

WEB TOOL TAIL

PART CODE: **WTTO-10** | **WTTO-15** | **WTTO-20**



**HEIGHT
SAFETY**

PRODUCT INFORMATION >

10cm Web tool tail - WTTO-10. Comes in a pack of 3.

15cm Web tool tail - WTTO-15. Comes in a pack of 3.

20cm Web tool tail - WTTO-20. Comes in a pack of 3.

PRODUCT FEATURES >

- Hi-Vis orange tail for easy visual location
- Contrast stitching

PRODUCT DETAILS >

- **D-Ring Material:** Electroplated zinc alloy
- **Webbing Material:** Polyester
- **Weight:** 15 grams (WTTO-10+WTTO-15) or 20 grams (WTTO-20)
- **Length:** 10cm, 15cm or 20cm
- **Secure with Silicone Tape:** ST

TOOL LANYARD INSTRUCTIONS >

- **Tether Point:** Begin with a tether point on the tool itself. As many tools don't have an attachment point for a tool lanyard, LINQ have developed tether points that can be retrofitted to any tool without causing damage or limiting its use.
- **Tool Lanyard:** There are different types of tool lanyards for different equipment, tasks and environments. Its important to assess both your tools and where they'll be used to decide which kind of lanyard is most suitable. You may want to have several types and lengths of lanyards to allow you to use your tools in various scenarios without any difficulty.
- **Anchor Point:** The anchor point needs to be just as robust as the rest of the system. For lighter tools, they can be secured to a wristband, a workbelt or to a harness worn by the worker. Heavier items should be tethered to a strong, fixed point such as a load rated rail or beam.

SUITABLE WITH >



ST



WTTO-10

WTTO-15

WTTO-20



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM