

# CONFINED SPACE RESCUE KIT

PART CODE: **CONFKIT24**



The LINQ Confined Space Rescue Kit is designed specifically for rescue from confined spaces. The kit can be quickly set up by one person and is easy to transport. The 25m wire rope winch is ideally suited to rescue applications and confined space work, with manual winding to raise or lower the worker up to 25m. Supplied with a tripod mounting bracket. Complies with AS/NZS 1891 and AS 2865:2009.

## KIT INCLUDES >



### **HSTP24** CONFINED SPACE ENTRY TRIPOD

- Adjustable height: 1.35m - 2.4m
- Footprint: 1.14m min - 2.10m max
- Lifting load capacity: 400kg
- Weight: 20kg ± 10gm
- Dual anchorage points rated at 15kN.
- Certified to EN 795:2012 Type B.



### **HSMW25** RESCUE-WORK POSITIONING WINCH

- For use with LINQ Confined Space Entry Tripod (HSTP24).
- Maximum lifting length: 25m
- Static Strength: 11.4kN for 3 minutes
- 170kg rating in accordance to EN:1496:2017.



### **H201** TACTICIAN RIGGERS HARNESS

- Pebble Weave Webbing.
- Slotted Pass Through Buckles.
- Integrated Suspension Trauma Strap.
- Shoulder Confined Space/ Rescue Loops.
- Large Dorsal Dee Ring.
- Front Belay Loops.



### **KSGA18** 2 x SCREW GATE KARABINERS

• Opening: 18mm	• Width: 58mm
• Weight: 165gm	• Length: 110mm
• Rating: 25kN	



### **HSCSSB** CONFINED SPACE SPREADER BAR

- For use with harnesses featuring confined space loops or D-rings.
- Ideal for confined space entry/exit, rescue, retrieval and recovery.
- Supplied with snap hook attachments to secure the worker.



### **HSKB710** KIT BAG

- Heavy-duty waterproof duffle kit bag.
- Secures and protects equipment between uses.
- Dimensions: 720mm x 320mm x 135mm.



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.